Docket No. 290167US-9350-9350-0-PCT Preliminary Amendment

## IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Original): A coolant line which comprises the following layers:

- I. an outer layer comprising a polyamide molding composition and
- II. an inner layer comprising polypropylene and at least 0.02% by weight of a heat stabilizer.

Claim 2 (Original): The coolant line as claimed in claim 1, wherein the layers I. and II. are joined to one another via a bonding layer.

Claim 3 (Original): The coolant line as claimed in claim 1, wherein the material of the inner layer is adhesion-modified.

Claim 4 (Original): The coolant line as claimed in claim 1, wherein the inner layer is composed of two sublayers of which the one adjacent to the polyamide layer is adhesion-modified.

Claim 5 (Currently Amended): The coolant line as claimed in any of the preceding elaims claim 1, wherein the heat stabilizer is a sterically hindered phenol or a sulfur compound.

Claim 6 (Currently Amended): The coolant line as claimed in any of the preceding elaims claim 1, wherein the molding composition of the inner layer or one of the inner sublayers contains from 0.1 to 50% by weight of a nanosize filler.

2

Docket No. 290167US-9350-9350-0-PCT Preliminary Amendment

Claim 7 (Currently Amended): The coolant line as claimed in any of the preceding elaims claim 1, wherein the molding composition of the inner layer or one of the inner sublayers comprises a metal deactivator.

Claim 8 (Currently Amended): The coolant line as claimed in any of the preceding elaims claim 1, wherein the polypropylene of the layer II. has a melt flow rate (MFR) in accordance with ISO 1133 (230°C/2.16 kg) in the range from 0.1 to 3 g/10 min.

Claim 9 (Currently Amended): The coolant line as claimed in any of the preceding elaims claim 1, wherein the polypropylene of the layer II. is a heterophase copolymer of propene and ethene.

Claim 10 (Original): The coolant line as claimed in claim 9, wherein the heterophase copolymer contains at least 0.5% by weight and not more than 20% by weight of ethene in copolymerized form.

Claim 11 (Currently Amended): The coolant line as claimed in any of the preceding elaims claim 9, wherein the layer II. has a thickness of at least 0.3 mm.

Claim 12 (Currently Amended): The coolant line as claimed in any of the preceding elaims claim 1 which is corrugated in subsections or in its entirety.

Claim 13 (Original): The coolant line as claimed in claim 12 which is configured as a corrugated pipe having a smooth inner layer.